



## *Frameless LED Panel light*

-100lm/w version



## ➔ Brief Introduction



### Frameless led panel light.

On/off, Casambi, Triac, DALI dim available

3T PMMA and 5T PMMA are available

PC diffuser, PMMA diffuser available

UGR>21 and UGR<19 available

Motion sensor, emergency available.

Instant start, no noise, no flickering

Environment friendly, without Mercury/hazardous substances

### Attention:

Do not look directly at LED light source for a long time.


In case of electric shock, please make sure the power is off before installation.

Please follow the correct installation steps to install the product, and do not touch when it is working.

The lamp should be installed and operated by a qualified electrician or technician in accordance with relevant local codes.

Unpack and examine the product carefully. Report any damage and save all packing materials if any portion of the product was damaged during transportation.

## ➔ Dimension Drawing



Model	A	B	C
300 x 300	295	295	17
300 x 600	595	295	17
600 x 600	595	595	17
620 x 620	620	620	17
300 x 1200	1200	300	17



## ➔ Technical specification



Model	Power	Led Q'ty	CCT	Lumen efficiency
300 x 300	20W	120pcs	3000K	95lm/w
			4000K	100lm/w
			6000K	102lm/w
300 x 600	26W	168pcs	3000K	95lm/w
			4000K	100lm/w
			6000K	102lm/w
600 x 600	36-40W	240pcs	3000K	95lm/w
			4000K	100lm/w
			6000K	102lm/w
620 x 620	36-40W	240pcs	3000K	95lm/w
			4000K	100lm/w
			6000K	102lm/w
300 x 1200	36-40W	240pcs	3000K	95lm/w
			4000K	100lm/w
			6000K	102lm/w

Item	Parameter
Input Voltage	AC200-240V
CRI	RA80/RA90
Beam Angle	120
Working Voltage	DC36-42V
Starting time.	<0.5S
IP Class	IP20
Warranty	5 years
Mac Adam	<5


## ➔ Photometric diagram



AVERAGE BEAM ANGLE (50%): 113.1DEG

UNIT: cd


- C0/180, 113.8 deg
- C30/210, 113.3 deg
- C60/240, 112.9 deg
- C90/270, 112.7 deg




Height Eavg/Emax Angle: 114.64deg Diameter

## ➔ Connection

Standard connection




Dimmable connection




## ➔ Installation

Suspended installation.



## ➔ Package



	Q'ty/CTN	N.W. /PCS (kg)	Size(mm)/Inner box	Size(mm)/CTN	G.W. (kg)/CTN
600 x 600	4pcs	4.60kg	690*680*55	700*700*240	20.00
620 x 620	4pcs	4.80kg	710*710*55	720*720*240	21.00
300 x 1200	4pcs	4.80kg	385*1280*55	400*1300*240	21.00